

			Country Coach Alignment Specifications Front - Neway IFS 144		
Before Alignment	Post Alignment		Target	Min.	Max.
0.9°	0.8°	Left Camber	0.50°	0.30°	0.70°
-0.6°	-0.1°	Right Camber	0.50°	0.30°	0.70°
1.4°	0.9°	Cross Camber	0.00°	-0.40°	0.40°
2.2°	2.6°	Left Caster	2.75°	1.75°	3.75°
2.1°	2.6°	Right Caster	2.75°	1.75°	3.75°
0.1°	0.0°	Cross Caster	0°	-1.00°	1.00°
0.03°	0.02°	Left Toe	.02"	.02"	.02"
0.04°	0.04°	Right Toe	.02"	.02"	.02"
0.07°	0.06°	Total Toe	.04"	.04"	.04"
16.1°	16.9°	SAI	6.50°	5.50°	7.50°
	16.8°	Included Angle	7.00°	5.75°	8.00°
0.12°	0.16°	Front Set Back	0.00°	-0.20°	+0.20°
			Country Coach Alignment Specifications Rear - Neway ADL-120		
0.10°	0.10°	Thrust Angle	0.00°	-0.06°	+0.06°
		Rear Offset	0.00°	-1/8"	+1/8"
0.4° Left -1.0° Right	0.4° Left -1.0° Right	Rear Camber	0.00°	-.050°	+0.50°
0.04° Left -0.16° Right	0.03° Left -0.16° Right	Rear Toe	0.00°	-0.15"	+0.15"
-0.12°	-0.13°	Rear Total Toe	0.00°	-0.30"	+0.30"